

# semproc — LaTeX class for seminar proceedings\*

Tobias Columbus<sup>†</sup>

Released 2015/06/15

## 1 Documentation

The class `semproc` is derived from KOMA-Script's class `scrreprt`. In addition to `scrreprt`'s many features, it provides `\talk` as an alternative to the `\chapter` command and some means to have a table of contents and a bibliography for each such `\talk`. Currently, `semproc` supports German and English.

### 1.1 Macros

<code>\talk</code>	<code>\talk</code> [ <i>speaker=</i> { <i>Speaker</i> }, <i>notes=</i> { <i>Typist</i> }] <i>{title}</i> starts a new talk with title <i>title</i> , speaker <i>Speaker</i> and typist <i>Typist</i> . The <code>\talk</code> macro also starts a new <code>biblatex</code> -refsection.
<code>\globaltoc</code>	<code>\globaltoc</code> typesets a global table of contents consisting of the various talks and its speakers.
<code>\localtoc</code>	<code>\localtoc</code> typesets a local table of contents consisting of the sections and subsections in the current talk.
<code>\localbib</code>	<code>\localbib</code> typesets a bibliography for the current talk.
<code>\nonumchapter</code>	<code>\nonumchapter</code> <i>{title}</i> starts a new unnumbered <code>\chapter*</code> with <i>title</i> but makes sure the chapter occurs in the global table of contents. More precisely, <code>\nonumchapter</code> is just a wrapper around <code>\chapter*</code> and <code>\etoccontentsline*</code> .

### 1.2 Environments

`summary` The `summary` environment is a drop-in replacement for the `abstract` environment.

### 1.3 Customization

`semproc` allows for customization of the fonts used in the heading of a talk and in the local and global table of contents. The fonts may be customized with

---

\*This file describes version v0.1, last revised 2015/06/15.

<sup>†</sup>E-mail: tobias.columbus@kit.edu

Font	Usage	Default
talkhead	Font of the head of a talk heading, i.e. the line “Talk 3”.	<code>\usekomafont {disposition}</code> <code>\usekomafont {section}</code>
talktitle	Font of the title of a talk	<code>\usekomafont {disposition}</code> <code>\usekomafont {chapter}</code>
talkspeakers	Font of the speaker and typist of a talk	<code>\usekomafont {disposition}</code>
globaltocspeaker	Speaker in an entry in the global table of contents	<code>\sffamily</code>
globaltocnumber	Number of an entry in the global table of contents	<code>\usekomafont {disposition}</code>
globaltoctitle	Title of an entry in the global table of contents	<code>\usekomafont {disposition}</code>
globaltocpage	Page number of an entry in the global table of contents	<code>\usekomafont {disposition}</code>
localtocheading	Heading of the local table of contents typeset with <code>\localtoc</code>	<code>\usekomafont {disposition}</code>
localtocnumber	Number of an entry in the local table of contents	<code>\sffamily</code>
localtoctitle	Title of an entry in the local table of contents	<code>\sffamily</code>
localtocpage	Page number of an entry in the local table of contents	<code>\sffamily</code>
summaryheading	Font for the heading of a <code>summary</code> environment	<code>\usekomafont {disposition}</code>

Table 1: Fonts that can be customized.

`\setkomafont` or `\addtokomafont` as described in the documentation of KOMA-Script. All fonts are shown in table 1.

## 1.4 Packages

`semproc` loads the following packages: `xkeyval`, `xcolor` `etoc`, `hyperref`, `bookmark`, `etoolbox`, `biblatex` and `csquotes`. Moreover, it passes the option `dvipsnames` to the package `xcolor`, which is loaded automatically by `hyperref`. For the precise arguments to these packages, the reader is referred to the implementation.

Note however, that bibliographies should be typeset using `biblatex` as opposed to `bibtex`.

## 1.5 Example

An example can be found in the file `example.tex`.

## 2 Implementation

```
1 (*class)
```

**scrreprt** Load `scrreprt` and pass all options to `scrreprt`.

```
2 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{scrreprt}}
3 \ProcessOptions\relax
4 \LoadClass{scrreprt}
```

**Packages** We load `xkeyval` for processing the names of the speaker/typist of each talk.

```
5 \RequirePackage{xkeyval}
```

We load `xcolor` and pass option `dvipsnames` as we set `RoyalBlue` as default colour for all links.

```
6 \PassOptionsToPackage{dvipsnames}{xcolor}
7 \RequirePackage{xcolor}
```

We load `etoc` for creating the macros for the local table of contents per talk and the global table of contents.

```
8 \RequirePackage{etoc}
```

We load `hyperref` for references. Option `hypertexnames` must be set to `false`, otherwise referencing the talks is buggy – at least the last time I tried.

```
9 \RequirePackage%
10 [unicode=true,colorlinks=true,hypertexnames=false]
11 {hyperref}
12 \RequirePackage{bookmark}
13 \hypersetup{allcolors={RoyalBlue}}
```

We load `etoolbox` for `\ifdefvoid` used in `\semproc@talk@head`.

```
14 \RequirePackage{etoolbox}
```

We load `biblatex` for managing bibliographies per talk via `refsections` and `csquotes` as it is recommended by `biblatex`.

```
15 \RequirePackage{biblatex}
16 \RequirePackage{csquotes}
```

**Internationalization** Using `\providecaptionname` of KOMA-Script, we define language dependent strings. Currently only German and English are supported.

We first define the german variants:

```
17 \providecaptionname{german,ngerman}%
18 {\talkname}{Vortrag}
19 \providecaptionname{german,ngerman}%
```

```

20 {\notesname}{Notizen von}
21 \providecaptionname{german,ngerman}%
22 {\nospeakername}{Kein Vortragender}
23 \providecaptionname{german,ngerman}%
24 {\localtoheadingname}{Inhalt}
25 \providecaptionname{german,ngerman}%
26 {\summaryname}{Zusammenfassung}

```

Next, we define the english variants:

```

27 \providecaptionname{USenglish,UKenglish,english}%
28 {\talkname}{Talk}
29 \providecaptionname{USenglish,UKenglish,english}%
30 {\notesname}{Notes by}
31 \providecaptionname{USenglish,UKenglish,english}%
32 {\nospeakername}{No speaker}
33 \providecaptionname{USenglish,UKenglish,english}%
34 {\localtoheadingname}{Contents}
35 \providecaptionname{USenglish,UKenglish,english}%
36 {\summaryname}{Abstract}

```

**Fonts** Using KOMA-Script's `\newkomafont`, we define various fonts that we use in this class. First, we define the fonts `talkhead`, `talktitle` and `talkspeakers`, which are used for the heading, i.e. the line "Talk 1", title and speakers/typists of the respective talk.

```

37 \newkomafont{talkhead}
38 {\usekomafont{disposition}\usekomafont{section}}
39 \newkomafont{talktitle}
40 {\usekomafont{disposition}\usekomafont{chapter}}
41 \newkomafont{talkspeakers}
42 {\usekomafont{disposition}}

```

Next, we define the fonts `globaltocspeaker`, `globaltocnumber`, `globaltocpage` and `globaltoctitle`, which are used for the speaker, number, page and title of the talk in the global table of contents.

```

43 \newkomafont{globaltocspeaker}
44 {\sffamily}
45 \newkomafont{globaltocnumber}
46 {\usekomafont{disposition}}
47 \newkomafont{globaltocpage}
48 {\usekomafont{disposition}}
49 \newkomafont{globaltoctitle}
50 {\usekomafont{disposition}}

```

Similarly, we define the fonts `localtocnumber`, `localtocpage`, `localtoctitle` for the local table of contents. Additionally, we define `localtocheading`, which is the font of the heading of the local table of contents.

```

51 \newkomafont{localtocheading}
52 {\usekomafont{disposition}}
53 \newkomafont{localtocnumber}

```

```

54 {\sffamily}
55 \newkomafont{localtocpage}
56 {\sffamily}
57 \newkomafont{localtoctitle}
58 {\sffamily}

```

Finally, we define the font `summaryheading`, which is the font of the heading of the `summary` environment also defined in this class.

```

59 \newkomafont{summaryheading}
60 {\usekomafont{disposition}}

```

`\nonumchapter` `\nonumchapter{<title>}` is a thin wrapper around `\chapter*` and `\etoccontentsline*`.

```

61 \newcommand{\nonumchapter}[1]{%
62   \chapter*{#1}%
63   \etoccontentsline*{chapter}{#1}{0}%
64 }

```

`Talk counter` A new counter for the talks.

```

65 \newcounter{talk}
66 \setcounter{talk}{0}

```

Compatibility with `autoref`.

```

67 \def\talkautorefname{\talkname}

```

We let sections be numbered within the talk, equations within the section and without referring to the chapter. The latter is achieved by redefining `\thesection` and `\theHsection` for `hyperref`.

```

68 \@addtoreset{section}{talk}
69 \@addtoreset{equation}{section}
70 \renewcommand\thesection{\arabic{section}}
71 \renewcommand\theHsection{\arabic{section}}
72 \renewcommand\theequation{\thesection.\arabic{equation}}

```

`\semproc@talk@head` The macro `\semproc@talk@head{<title>}` typesets the heading of the talk with the given title. The counter `talk` has to be incremented and the values of `\semproc@talk@speaker` and `\semproc@talk@notes` have to be set before calling `\semproc@talk@head`.

```

73 \newcommand{\semproc@talk@head}[1]{%
74   {\noindent\usekomafont{talkhead}\talkname~\thetalk}%
75   {\par\nobreak\vskip2ex}%
76   {\usekomafont{talktitle}\noindent#1}
77   \vskip1ex\noindent\hrulefill\vskip1ex
78   {
79     \usekomafont{talkspeakers}
80     \noindent\semproc@talk@speaker%
81     \ifdefvoid{\semproc@talk@notes}{-}{%
82       \hfill{\notesname~\semproc@talk@notes}%
83     }

```

```

84   \par\nobreak%
85   }%
86   \vskip 3.5ex
87 }

```

`\talk` The main macro of this class is `\talk [speaker=Speaker, notes=Notes] {title}` intended to replace `\chapter`. We first prepare the optional key/value options.

```

88 \define@key{talk}{speaker}%
89   [\nospeakername]%
90   {\def\semproc@talk@speaker{#1}}
91 \define@key{talk}{notes}%
92   []%
93   {\def\semproc@talk@notes{#1}}

```

The macro `\talk` parses the key/value options, increments the counter `talk` and calls `\semproc@talk@head` for typesetting the heading. Finally, it starts a new biblatex refsection and writes all the data to the `.aux` file via `etoc`'s `\etoccontentsline` macro. The `\@currentlabelname` is set for correct references.

```

94 \newcommand*\talk[2] [\empty]{%
95   \presetkeys{talk}{speaker,notes}{}%
96   \setkeys{talk}{#1}%
97   \refstepcounter{talk}%
98   \cleardoubleoddplainpage%
99   \thispagestyle{\chapterpagestyle}%
100  \semproc@talk@head{#2}
101  \renewcommand\@currentlabelname{#2}
102  \newrefsection%
103  \etoccontentsline*{talk}%
104    {\protect\numberline{\thetalk}#2}{0}
105  \etoccontentsline{speaker}%
106    {\protect\numberline{}\semproc@talk@speaker}
107  \renewcommand\@currentlabelname{#2}
108 }

```

`Various lengths and a box` Lengths for typesetting the local and global tables of contents.

```

109 \newlength{\semproc@toc@skip}
110 \setlength{\semproc@toc@skip}{4em}
111 \newlength{\semproc@toc@calc}

```

`\semproc@toc@skipafter` `\semproc@toc@skipafter {style}` typesets `\etocnumber` with the chosen `style` and then skips the difference of `\semproc@toc@skip` and the width of `\etocnumber`.

```

112 \newcommand\semproc@toc@skipafter[1]{%
113   \settowidth{\semproc@toc@calc}%
114     {#1\etocthenumber}%
115   \addtolength{\semproc@toc@calc}%
116     {-\semproc@toc@skip}%
117   \setlength{\semproc@toc@calc}%

```

```

118     {-\semproc@toc@calc}%
119     \noindent{#1\etocnumber}%
120     \hskip\semproc@toc@calc%
121 }

```

`\globaltoc` `\globaltoc` prints out a global table of contents showing only the talks and the respective speakers/typists.

```

122 \newcommand{\globaltoc}{%
123   \beginingroup
124     \etocsetnexttocdepth{1}
125     \etocsetlevel{speaker}{1}
126     \etocsetlevel{section}{2}
127     \etocsetlevel{talk}{0}
128     \etocsetlevel{chapter}{0}

```

The speaker is written below the title of the talk with `\semproc@toc@skip` indentation and font `globaltocspeaker`.

```

129     \etocsetstyle{speaker}
130     {}
131     {}
132     {%
133       \hskip\semproc@toc@skip%
134       {\usekomafont{globaltocspeaker}\etocthename}%
135       \nobreak\hfill\nobreak\par%
136     }
137     {}

```

Before each talk entry in the global table of contents, we have a vertical skip of `1ex`. Then, the number of the talk is written left-aligned and the title of the talk is written on the same line with indentation `\semproc@toc@skip`.

```

138     \etocsetstyle{talk}
139     {}
140     {\vskip1ex\leavevmode\relax}
141     {%
142       \semproc@toc@skipafter{\usekomafont{globaltocnumber}}%
143       {%
144         \usekomafont{globaltoctitle}%
145         \etocname%
146       }%
147       \nobreak%
148       \leaders\hbox to .3cm{\hss.}\hfill%
149       \nobreak%
150       \makebox[1cm][r]{%
151         \usekomafont{globaltocpage}%
152         \hss\etocpage%
153       }\par%
154     }
155     {}
156 \tableofcontents

```

```

157 \endgroup
158 }

```

`\localtoc` `\localtoc` prints out a local table of contents consisting only of the sections and subsections in the current talk.

```

159 \newcommand{\localtoc}{%
160 \begingroup
161 \let\parskip@old%
162 \parskip\parskip0ex%
163 \etocsetnexttocdepth{2}
164 \etocsetlevel{section}{1}
165 \etocsetlevel{subsection}{2}
166 \etocsetlevel{talk}{-2}
167 \etocsetlevel{speaker}{-2}
168 \etocsetlevel{chapter}{-2}

```

Every section except the first one has a `\vskip` of `1ex` before it is typeset. Then, sections are written with `\semproc@toc@skip` indentation.

```

169 \etocsetstyle{section}
170 {}
171 {%
172 \ifthenelse{\equal{\etocthenumber}{1}}{%
173 {}%
174 {\vskip1ex}%
175 }
176 {%
177 \semproc@toc@skipafter{%
178 \usekomafont{localtocnumber}%
179 }%
180 {%
181 \usekomafont{localtoctitle}%
182 \etocname%
183 }%
184 \nobreak%
185 \leaders\hbox to .3cm{\hss.}\hfill%
186 \nobreak%
187 \makebox[1cm][r]{%
188 \usekomafont{localtocpage}%
189 \hss\etocpage%
190 }\vskip0.5ex%
191 }
192 {}

```

Subsections are written with `\semproc@toc@skip` indentation and no additional vertical space.

```

193 \etocsetstyle{subsection}
194 {}
195 {}
196 {}

```



```

197     \semproc@toc@skipafter{%
198         \usekomafont{localtocnumber}%
199     }%
200     {%
201         \usekomafont{localtoctitle}%
202         \etocname
203     }%
204     \nobreak%
205     \leaders\hbox to .3cm{\hss.}\hfill%
206     \nobreak%
207     \makebox[1cm][r]{%
208         \usekomafont{localtocpage}%
209         \hss\etocpage%
210     }\vskip0.5ex%
211 }
212 {}

```

Finally, we define the heading of the table of contents and typeset it.

```

213     \etocsettocstyle{%
214         \centerline{%
215             \usekomafont{localtocheading}%
216             \localtocheadingname%
217         }
218     }{}
219     \localtableofcontents
220     \parskip\parskip@old
221     \endgroup
222 }

```

**summary** Instead of using the `abstract` environment, we define a `summary` environment to be used for each talk.

```

223 \newenvironment{summary}
224     {%
225         \centerline{%
226             \usekomafont{summaryheading}%
227             \summaryname%
228         }%
229     \let\parindent@old\parindent\parindent0em%
230     }{%
231         \parindent\parindent@old\vskip3.5ex%
232     }

```

`\localbib`

```

233 \newcommand{\localbib}{%
234     \printbibliography[heading=subbibliography]%
235 }

```

```

236 </class>

```

### 3 Change History

v0.1

General: First public release . . . . . 1

### 4 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

<b>Symbols</b>	127, 128, 164,	<code>\let</code> . . . . . 161, 229
<code>\@addtoreset</code> . . . . . 68, 69	165, 166, 167, 168	<code>\LoadClass</code> . . . . . 4
<code>\@currentlabelname</code> . . . . . 101, 107	<code>\etocsetnexttocdepth</code> . . . . . 124, 163	<code>\localbib</code> . . . . . <i>1</i> , 233
<b>A</b>	<code>\etocsetstyle</code> . . . . . 129, 138, 169, 193	<code>\localtableofcontents</code> . . . . . 219
<code>\addtolength</code> . . . . . 115	<code>\etocsettocstyle</code> . . . . . 213	<code>\localtoc</code> . . . . . <i>1</i> , 159
<code>\arabic</code> . . . . . 70, 71, 72	<code>\etocthename</code> . . . . . 134	<code>\localtocheadingname</code> . . . . . 24, 34, 216
<b>B</b>	<code>\etocthenumber</code> 114, 172	<b>M</b>
<code>\begingroup</code> . . . . . 123, 160	<code>\etoccontentsline</code> . . . . . 63, 103, 105	<code>\makebox</code> . . . . . 150, 187, 207
<b>C</b>	<b>F</b>	<b>N</b>
<code>\centerline</code> . . . . . 214, 225	<code>\Fonts</code> . . . . . 37	<code>\newcommand</code> 61, 73, 94, 112, 122, 159, 233
<code>\chapter</code> . . . . . 62	<b>G</b>	<code>\newcounter</code> . . . . . 65
<code>\chapterpagestyle</code> . . . . . 99	<code>\globaltoc</code> . . . . . <i>1</i> , 122	<code>\newenvironment</code> . . . . . 223
<code>\cleardoubleoddplainpage</code> . . . . . 98	<b>H</b>	<code>\newkomafont</code> . . . . . 37, 39, 41, 43, 45, 47, 49, 51, 53, 55, 57, 59
<code>\CurrentOption</code> . . . . . 2	<code>\hbox</code> . . . . . 148, 185, 205	<code>\newlength</code> . . . . . 109, 111
<b>D</b>	<code>\hfill</code> . . . . . 82, 135, 148, 185, 205	<code>\newrefsection</code> . . . . . 102
<code>\DeclareOption</code> . . . . . 2	<code>\hrulefill</code> . . . . . 77	<code>\nobreak</code> . . . . . 75, 84, 135, 147, 149, 184, 186, 204, 206
<code>\def</code> . . . . . 67, 90, 93	<code>\hskip</code> . . . . . 120, 133	<code>\noindent</code> . . . . . 74, 76, 77, 80, 119
<code>\define@key</code> . . . . . 88, 91	<code>\hss</code> . . . . . 148, 152, 185, 189, 205, 209	<code>\nonumchapter</code> . . . . . <i>1</i> , 61
<b>E</b>	<code>\hypersetup</code> . . . . . 13	<code>\nospeakername</code> 22, 32, 89
<code>\empty</code> . . . . . 94	<b>I</b>	<code>\notesname</code> . . . . . 20, 30, 82
<code>\endgroup</code> . . . . . 157, 221	<code>\ifdefvoid</code> . . . . . 81	<code>\numberline</code> . . . . . 104, 106
environments:	<code>\ifthenelse</code> . . . . . 172	<b>P</b>
summary . . . . . <i>1</i> , 223	<code>\Internationalization</code> . . . . . 17	<code>\Packages</code> . . . . . 5
<code>\equal</code> . . . . . 172	<b>L</b>	<code>\par</code> . . . . . 75, 84, 135, 153
<code>\etocname</code> . . . . . 145, 182, 202	<code>\leaders</code> . . . . . 148, 185, 205	
<code>\etocnumber</code> . . . . . 119	<code>\leavevmode</code> . . . . . 140	
<code>\etocpage</code> . . . . . 152, 189, 209		
<code>\etocsetlevel</code> . . . . . 125, 126,		

